



ELESA Original design MBT

1 d_1		2 d_2		2 d_3 H9		2 d_4		2 h_1		2 h_2		2 t_1		2 t_2	
Nominal dimension	Actual dimension	Thread	Bore					min.		min.		min.		min.	
32	31	M 5	-	15	24	11,5	10	-							
32	31	M 6	-	15	24	11,5	12	-							
40	39,5	M 6	B 6	17	26,5	12,5	12	14							
40	39,5	M 8	-	17	26,5	12,5	13	-							
50	50	M 8	B 8	20	33	16	20	20							
50	50	M 10	-	20	33	16	18	-							
60	61	M 10	B 10	23	39	18,5	20	25							
60	61	M 12	-	23	39	18,5	20	-							
70	70	M 12	-	24	42	20,5	20	-							
70	70	M 14	-	24	42	20,5	20	-							

Specification

- Plastic
Technopolymer (Polypropylene PP)
- reinforced, shock-resistant
- temperature resistant up to 90 °C
- black, RAL 9005, matte ● **SW**
- Bushing
Brass
- Color of the cover cap (matte):
black, RAL 9005 —
red, RAL 3000 ● **DRT**
- ISO-Fundamental tolerances
→ Main Catalogue Page 1479
- Cross holes GN 110
→ Main Catalogue Page 1422
- Plastic characteristics
→ Main Catalogue Page 1483

• RoHS

On request

- Cover cap in further colors

Information

The unique profile (small squares) on the rim of the knurled knobs GN 534 is characteristic of its form and the function.

see also...

- Control handwheels GN 735 → Main Catalogue Page 214
- Knurled knobs GN 7336 → Main Catalogue Page 444
- Knurled knobs GN 534 with loss protection GN 111.7
→ Main Catalogue Page 1426

How to order (with cover cap black)	1 d_1
	2 d_2 (d_3)
GN 534-40-M8-SW	3 Color knob

How to order (with cover cap red)	1 d_1
	2 d_2 (d_3)
GN 534-50-M8-SW-DRT	3 Color knob
	4 Color cover cap