



ROSTFREI
Inox
Stainless
Steel

Inch
sizes
available

4 Type

- A** without bore (unmachined)
- B** with through bore H7
- C** with blind bore H7
- D** with threaded through bore
- E** with threaded blind bore

2			3	3								
d ₁	GG	NI	AL	d ₂ Thread Type D Type E	d ₃ H7 Bore Type B Type C	d ₄	h ₁ Type B, C, D, E	h ₂ Type B, C, D, E	h ₃ Type A	h ₄ Type A	t ₁ min.	t ₂
32	32	-	-	M 6	B 6	12	20	9	21	10	12	10
40	40	40	-	M 8	B 8	14	25	13	26	14	15	13
50	50	50	-	M 10	B 10	18	32	18	34	20	18	16
63	63	63	-	M 12	B 12	20	40	23	42	25	22	20
80	-	80	-	M 16	B 16	25	50	28	52	30	28	20
100	-	-	-	M 20	B 20	32	63	36	65	38	36	25

Specification

- Cast iron
fettled and tumbled **GG**
- Stainless Steel-
Precision casting
only Types A, C, D, E
- AISI CF-8
- matte shot-blasted **NI**
- Aluminum
forged
only Types A, C, D, E
- matte finish (ground)
flash mark not visible **MT**
- polished **PL**
- ISO-Fundamental tolerances → Page 1479
- Stainless Steel characteristics → Page 1489
- RoHS

On request

- plastic coated

Information

see also...

- Hand knobs DIN 6335 (Plastic) → Page 422
- Hand knobs GN 6335.1 (Duroplast, with protruding steel bushing) → Page 424
- Hand knobs GN 6335.2 (Technopolymer, with protruding steel bushing) → Page 424
- Hand knobs DIN 6335 with loss protection GN 111.7 → Page 1426

How to order (without bore, matte)

1 Material

2 d₁

3 **2** **4**

DIN 6335-AL-63-A

4 Type

How to order (Cast iron)

1 Material

2 d₁

3 d₂ (d₃)

4 Type

1 **2** **3** **4**

DIN 6335-GG-63-M12-D

How to order (Aluminum)

1 Material

2 d₁

3 d₃ (d₂)

4 Type

5 Finish

1 **2** **3** **4** **5**

DIN 6335-AL-50-B10-C-MT