



ELESA original design MBT+I



Type

D with revolving knob

1

2

d_1	d_2 H9 Bore	d_3	d_4	d_5	b	l_1	l_2	l_3	l_4	r
40	B 6	17	M 4	13,5	14	26,5	14	20	4	10,25
50	B 6	20	M 5	13,5	17	33	18	20	5	14
60	B 8	23	M 5	16	20,5	39	20	23	6	19
70	B 10	24	M 5	16	21,5	42	25	23	6	24
85	B 10	29	M 5	16	20	30,5	22	23	6	31,5
100	B 10	35	M 5	16	20	31	22	23	6	39

Specification

- Plastic
Technopolymer (Polypropylene PP)
- reinforced, shock-resistant
- temperature resistant up to 90 °C
- black, matte
- Hub bushing
Brass
- Grub screw DIN 916
with internal hexagon and serrated point
- Revolving knobs GN 595
- Plastic, Technopolymer (Polyamide PA)
black, matte
- Spindle steel
zinc plated, blue passivated
- ISO-Fundamental tolerances → Page 1479
- Plastic characteristics → Page 1483
- RoHS compliant

On request

- Hub cap in other colors

Information

Control handwheels GN 735 are used for setting operations with low torque.

Coarse setting is made by means of the cylindrical handle (fingertip grip) followed by fine setting using the knurled rim of the handwheel.

see also...

- Control handwheels GN 736 (Aluminum black, anodized) → Page 212
- Control handwheels GN 736.1 (Aluminum black, anodized) → Page 213
- Clamping elements GN 826 (for adjustable spindles) → Page 268

How to order

 1 d_1
 2 d_2
 3 Type
GN 735-40-B6-D